

COMMISSION

Twenty-Second Regular Session

1 - 5 December 2025 Manila, Philippines (Hybrid)

HSBI Catch Quantification Guide

WCPFC22-2025-13b 1 November 2025

Voluntary HSBI Regional Guides
TOOLS FOR HIGH SEAS BOARDING AND INSPECTIONS





Voluntary HSBI Regional Guides

TOOLS FOR HIGH SEAS BOARDING AND INSPECTIONS

HSBI Catch Quantification Guide

Document History

Version	Effective Date	Description of Revision	Prepared by	Reviewed by
1.1	31 October	For WCPFC22 consideration	HSBI WG	HSBI WG Chair

Contents

PURPOSE STATEMENT	2			
Quantify and estimate catch weights in WCPFC HSBI activities.	3			
HSBI Catch quantification estimation				
Accessibility of Catch quantification method information				

PURPOSE STATEMENT

- 1. This document provides guidance to Authorised inspectors conducting WCPFC High Seas Boarding and Inspections (HSBI¹) on:
 - catch quantification, an estimation on the quantities of fish on board, when direct weighing or weighing by sampling is not possible
 - tools and methods for catch quantifications
 - the minimum standards for analysis.
- 2. The development of this Guide also aims to:
 - support the establishment of robust catch estimation methods to quantify and estimate the catch on board
 - ensure that catch estimates are credible and are consistently using appropriate methods and procedures.

¹ HSBI, refers to boarding, inspection, and related activities on the high seas within the Convention Area conducted pursuant to CMM 2006-08 Western and Central Pacific Fisheries Commission Boarding and Inspection Procedures or any successor CMM.

- 3. This guide refers to general considerations in the application of quantifying the catch² on board during a HSBI and the estimation and analysis process, which includes:
 - catch document³ analysis
 - freezer and Fish Hold inspections
 - verifying Catch
 - quantifying catch
 - weight estimations
 - analysis
 - reporting.
- 4. The application of this Guide will be voluntary and apply to HSBI activities within the WCPFC area of competence.
- 5. This guide can be modified in response to new information, technical innovations, and perspectives. It is expected that this guide will continue to evolve as the field develops.

Quantify and estimate catch weights in WCPFC HSBI activities.

- 6. The aim of HSBIs is to ensure compliance of a vessel with the WCPFC Convention and all applicable WCPFC CMM obligations.
- 7. A key function of an authorised inspectors during a HSBI is to identify potential misreporting, unreported transhipment, under reporting or record keeping errors.
- 8. Inspectors conducting HSBI activities can detect and confirm species on board at the time of inspection. They can do this by comparing the information in catch documents with a visual check, count or estimation of catch on board.
- 9. The purpose of quantifying catch is to verify what is declared on the log sheets is what is on board the fishing vessel. It is an important tool for Inspectors to assess if the catch is being recorded accurately, and in line with the relevant WCPFC CMMs.
- 10. The use of catch quantification during HSBI activities can assist with assessing compliance with vessel licensing and reporting obligations, including to:
 - verify catch reporting/ catch log data
 - estimate total catch held on the vessel
 - assist a risk assessment for a more extensive sampling i.e. Port inspection.
- 11. The general aim of catch quantification is to:
 - measure the hold as accurately as possible to calculate the total hold space
 - estimate the area of the hold filled with fish to estimate tonnage of fish
 - compare estimated tonnage with the amount of fish recorded in the fishing logbook

² Catch refers to the target, bycatch or non-bycatch species.

³ Catch documents can include logbooks, log sheets, observer reports, transhipment declarations, captain's notes, engineers' reports - both electronic or written.

- assess whether there is reasonable suspicion that non-compliances can be linked to tonnage inconsistency.
- 12. This is an initial estimate so Authorised Inspectors can check the logbook to identify any discrepancies. If discrepancies are found:
 - this may inform or call for a more accurate approach, such as a port inspection within the framework provided by WCPFC CMMs, or unload/offload, or;
 - inform the flag State and request an enquiry into the vessel.

HSBI Catch quantification estimation

Table 1. Methods of estimating catch quantity

Volumetrics	Subsample	Processed unit counts	
Estimate fish in the hold	weighing a subsample of	counting the total number of individual	
where the volume of the	a species then	(processed or whole), multiplied by the	
hold is known, or can	calculating average fish	average weight (or an estimated weight)	
be calculated	weight	to find the total weight of the species	

- 13. The most appropriate quantification method will depend on the type of vessel⁴, type of fish hold, and the amount of catch on board. It may be useful to use two methods in combination. Consider what fish are onboard, how they are stored and what information you have available to help decide what method(s) could assist.
- 14. The general principles and procedures for catch quantification in fisheries inspections:
 - documentation and records
 - information gathering
 - hold measurements: density and conversion factors
 - compare catch information to catch estimates.

a) Documentation and records

- 15. Authorised inspectors should:
 - document the catch quantification process including analysis, using photographs and videos
 - conduct the catch quantification process with witnesses' present (master and crew), where practicable.
 - ideally work in pairs or as a trio, to cover the tasks:
 - reviewing the logbooks and interviews the master for species, product types, and estimated catch
 - performing the necessary physical measurements in each fish hold for fish volume estimation.
- 16. The HSBI report should record any catch quantification estimation and analysis. The authorised inspector should record as much as possible, including but not limited to the following information:

⁴ The quantification method in paragraph 21 may not be applicable to fresh fish stowed in tuna longliners at this moment.

- date of the inspection
- vessel name
- vessel coordinates
- catch quantification methods, measurements (including unit of measurement), estimations, conversion factors and analysis.
- 17. The master of the vessel must be provided with an interim copy of the report which includes details of any catch quantification analysis. The master must also be given to opportunity to include any objection or comment to be included in the final report.

b) Procedural steps

- 18. Authorised inspectors should calculate the total cubic capacity of each cargo hold, measured in cubic metres. Information on the vessel cargo holds, freezer or storage areas can be found in various ships documents, and ideally, be certified by the CCM and valid:
 - Vessel Plans or Capacity Plan
 - **Hull Survey Certificates**
 - General Arrangements
 - Stability Book.
- 19. Authorised inspectors should check ships beam (width) for verification of vessels principal dimensions. This will confirm information on the plans belongs to that vessel.

c) Measuring the hold - volumetrics

- 20. To obtain the hold volume by measuring interior dimensions, Authorised inspectors can either, measure the volume occupied by the fish in the hold, or measure the free air space in the hold, and deduct it from the total cubic capacity of the hold (paragraph 18).
- 21. To obtain fish volume estimation by species, convert the fish volume into fish weight. The factors below are illustrative examples for the inspector's reference:
 - Apply density factors⁵. An estimate for the average density of whole fish in bulk is 1080kg/m3. Some examples (mean values):

Marlin (MLS): 1080 kg/m³

Bigeye tuna (BET): 1064 kg/m³

Pacific bluefin tuna (PBF): 1070 kg/m³

Albacore tuna (ALB): 1054 kg/m³

Skipjack tuna (SKJ): 1090 kg/m³

• Swordfish (SWO): 1075 kg/m³

Apply processing conversion factor⁶ if fish is processed, species by species. The following ii. conversion factors are some of the examples:

⁵ Magnuson, J. J. 1973. Comparative study of adaptations for continuous swimming and hydrostatic equilibrium of scombroid and xiphoid fishes. Fishery Bull. 71:337–356.

Species (FAO code)	Whole	Gutted	Gutted + Head off
Marlin (MLS)	1.00	1.10	1.30
Bigeye tuna (BET)	1.00	1.29	1.33
Pacific bluefin tuna (PBF)	1.00	1.16	1.36
Albacore tuna (ALB)	1.00	1.23	1.31
Skipjack tuna (SKJ)	1.00	1.10	1.29
Swordfish (SWO)	1.00	1.31	1.30
Sharks (CWZ)	1.00	1.10	2.00
Yellowfin tuna (YFT)	1.00	1.10	1.36

iii. Apply stacking factors⁷, taking into account if stacking is loose (factor 0.45), medium (factor 0.51, mean value for frozen tuna), or tight (factor 0.54).

Example Calculation

Hold: $8 \times 8 \times 2.5 \text{ m} = 160 \text{ m}^3$

Fill rate: 70%

Species: Bigeye tuna (BET), gutted

Density: 1064 kg/m³

Stacking factor: 0.51

Processing factor: 1.29

Usable volume: $160 \times 0.7 = 112 \text{ m}^3$

Gross weight = 112 × 1064 = 119168 kg

Stacked weight = $119,280 \times 0.51 = 60775,68 \text{ kg}$

Catch weight = $60775,68 \times 1.29 = 78400,6 \text{ kg} \approx 78,4 \text{ tonnes}$

d) Analysis of Results

- 22. Compare the estimation result with the fishing logbook, captain's declarations, and any landing or transhipment data. Calculate the data and assess whether there are significant differences between the figures.
 - If fishing logbook figure > catches onboard:

⁶ The Food and Agriculture Organization's (FAO) Coordinating Working Party on Fishery Statistics (CWP). Handbook of Fishery Statistics: Indicative factors for converting product weight to live weight for a selection of major fishery commodities.

⁷ Note that stacking factors vary depending on the type of fishing vessel (e.g. purse seine, longline, trawler).

- look for concealed space where fish could be stored
- look for evidence that an undeclared transshipment occurred during the fishing vessel trip, where the fishing vessel gave fish.
- If fishing logbook figure < catches onboard:
 - look for evidence that an undeclared transshipment occurred during the fishing vessel trip, where the fishing vessel received fish
 - look for species that might be underreported.

Accessibility of Catch quantification method information

- 23. To assist the catch quantification process during HSBI, it may be beneficial for the catch quantification procedures to be translated into languages that are in use on fishing vessels and/or as pictographs to bridge any language barriers.
- 24. Information accessibility of the HSBI Catch quantification process for the vessel master crew and for the HSBI Authorised inspectors could be supported via:
 - HSBI Multi-language cards
 - the catch quantification procedures given/shown to master of vessel by HSBI Authorised inspectors
 - the voluntary guide translated by CCMs.

